

ANGt101/RES

goniometer with resistive encoder for closed loop operation providing Θ -positioning

Technology	
travel mechanism	inertial piezo drive

Size and Dimensions	
footprint; height	24 x 24; 11 mm
maximum size (outer position)	24 x 26.4; 11.8 mm
distance center of rotation to bottom	51 mm (above center)

Coarse Positioning Mode	
travel (step mode)	6.6°
typical minimum step size	0.1 m° @ 300 K, 0.02 m° @ 4 K
maximum speed (@ 300 K, no load)	approx. 1 °/s

Fine Positioning Mode	
scan range	no fine positioning capability

Materials (non-magnetic)	
positioner body	Titanium (other materials on request)
actuator	PZT ceramics
connecting wires	insulated twisted pair, Cu
weight	18 g

Load	
maximum vertical load	100 g
maximum static forces along the axis	3 N
maximum dynamic force along the axis	2 N

Mounting	
frontside mounting	two through holes for M2
backside mounting	two threads M2.5 x 6 mm
load mounting	six threads M2 x 3 mm

Article Numbers			
/RT Version	1002792	/LT Version	1002798
/HV Version	1002794	/LT/HV Version	1002800
/UHV Version	1002796	/LT/UHV Version	1002802

Compatibility with Electronics	
ANC350 piezo controller	all versions

Working Conditions

mounting orientation	axis perpendicular to gravity
magnetic field range	0 .. 31 T
temperature range (/RT, /HV, /UHV)	0 .. 100 °C
temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 300 K
max. bake out temperature (/UHV, /LT/UHV)	150 °C
minimum pressure (/RT, /LT)	1E-4 mbar
minimum pressure (/HV, /LT/HV)	1E-8 mbar
minimum pressure (/UHV, /LT/UHV)	5E-11 mbar

Connectors and Feedthroughs	/RT, /LT Versions	all /HV, /UHV Versions
connector type	2-pole pin plug, ø 0.5 mm, d = 2 mm, 30 cm cable with connector	two female conn., for pin ø 1 mm, 30 cm cable with connector
electrical feedthrough solution	COC230/LT	COC230/HV, COC230/UHV
encoder connector	additional 3-pole plug	3 additional female connectors

Temperature Dependent Data

	@ 300K	@ 4K (only /LT versions)
input voltage range	0 .. +100 V	0 .. +100 V
typical actuator capacitance	1050 nF	150 nF
typical step size (min .. max)	0.1 .. 3 m°	0.02 .. 0.5 m°
fine positioning range	---	---

Accuracy of Movement

repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 %

Position Encoder

readout mechanism	resistive encoder, potentiometric measurement
encoded travel range	6.6°
sensor resolution	approx. 0.1 m°
repeatability	approx. 1-2 m°

