

ANPx101eXT12/RES

linear, horizontal stepper positioner with 12 mm travel range and resistive encoder for closed loop operation

Technology	
travel mechanism	inertial piezo drive

Size and Dimensions	
footprint; height	40 x 24; 11 mm
maximum size	40 x 24; 11 mm

Coarse Positioning Mode	
travel (step mode)	20 mm
typical minimum step size	50 nm @300K
maximum speed (@ 300 K, no load)	approx. 3 mm/s

Fine Positioning Mode	
scan range	7.5 µm @ 300 K, 1.2 µm @ 4 K
scan resolution	sub-nm resolution

Materials (non-magnetic)	
positioner body	Titanium (other materials on request)
actuator	PZT ceramics
connecting wires	insulated Cu wires
weight	25.5 g

Load	
maximum vertical load	200 g
maximum static forces along the axis	4 N
maximum dynamic force along the axis	2 N
maximum torque on the axis	20 Ncm

Mounting	
frontside mounting	four through holes for M2
backside mounting	four threads M2,5 x 4 mm
load mounting	six threads M2 x 3 mm

Article Numbers			
/RT Version	1004861	/LT Version	1004864
/HV Version	1004862	/LT/HV Version	1004865
/UHV Version	1004863	/LT/UHV Version	1004866

Compatibility with Electronics	
ANC350 piezo positioning controller	all versions

Working Conditions

mounting orientation	axis horizontal
magnetic field range	---
temperature range (/RT, /HV, /UHV)	0 .. 100 °C
temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 373 K
max. bake out temperature (/UHV, /LT/UHV)	150 °C
minimum pressure (/RT, /LT)	1E-4 mbar
minimum pressure (/HV, /LT/HV)	1E-8 mbar
minimum pressure (/UHV, /LT/UHV)	5E-11 mbar

Connectors and Feedthroughs	/RT, /LT Versions	all /HV, /UHV Versions
connector type	2-pole pin plug, Ø 0.5 mm, d = 2 mm,	2-pole pin plug (PEEK), Ø 0.5 mm, d = 2 mm,
connector type	30 cm cable with connector	30 cm cable with connector
electrical feedthrough solution	COC230/LT	COC230/HV, COC230/UHV
encoder connector	additional 3-pole plug	additional 3-pole plug (Peek)

Temperature Dependent Data	@ 300K	@ 4K (only /LT versions)
input voltage range	0 .. +100 V	0 .. +100 V
typical actuator capacitance	1550 nF	220 nF
typical step size (min .. max)	0.05 .. 3 µm	10 .. 500 nm
fine positioning range	7.5 µm	1.2 µm

Accuracy of Movement

repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 %

Position Encoder

readout mechanism	resistive encoder, potentiometric measurement
sensor power (when measuring)	< 1 mW possible
encoded travel range	full travel
sensor resolution	approx. 200 nm
repeatability	1 - 2 µm
linearity (over full travel)	1%

Drawings

