

ANPz101eXT12

linear, vertical stepper positioner providing highest stability with 12 mm extended travel range

Technology	
travel mechanism	inertial piezo drive

Size and Dimensions	
footprint; height	24 x 48; 11.5 mm
maximum size	24 x 48; 11.5 mm

Coarse Positioning Mode	
travel (step mode)	12 mm
typical minimum step size	50 nm @ 300 K, 10 nm @ 4 K
maximum speed (@ 300 K, no load)	approx. 3 mm/s

Fine Positioning Mode	
scan range	0 .. 7.5 µm @ 300 K, 0 .. 1.2 µm @ 4 K
scan resolution	sub-nm resolution

Materials (non-magnetic)	
positioner body	Titanium (other materials on request)
actuator	PZT ceramics
connecting wires	insulated twisted pair, Cu
weight	35 g

Load	
maximum vertical load	200 g
maximum static forces along the axis	8 N
maximum dynamic force along the axis	5 N
maximum torque on the axis	10 Ncm

Mounting	
frontside mounting	two through holes for M2
backside mounting	two threads M2,5 x 4 mm
load mounting	six threads M2 x 3 mm

Article Numbers			
/RT Version	--	/LT Version	--
/HV Version	--	/LT/HV Version	--
/UHV Version	--	/LT/UHV Version	--

Compatibility with Electronics	
ANC106 piezo step controller	all versions
ANC300 piezo positioning controller	all versions
ANC350 piezo positioning controller	all versions

Working Conditions	
mounting orientation	axis vertical
magnetic field range	0 .. 31 T
temperature range (/RT, /HV, /UHV)	0 .. 100 °C
temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 373 K
max. bake out temperature (/UHV, /LT/UHV)	150 °C
minimum pressure (/RT, /LT)	1E-4 mbar
minimum pressure (/HV, /LT/HV)	1E-8 mbar
minimum pressure (/UHV, /LT/UHV)	5E-11 mbar

Connectors and Feedthroughs	/RT, /LT Versions	all /HV, /UHV Versions
connector type	2-pole pin plug, Ø 0.5 mm, d = 2 mm,	2-pole pin plug (PEEK), Ø 0.5 mm, d = 2 mm,
connector type	integrated connector	30 cm cable with connector
electrical feedthrough solution	VFT/LT	VFT/HV, VFT/UHV

Temperature Dependent Data	@ 300K	@ 4K (only /LT versions)
input voltage range	0 .. +100V	0 .. +100V
typical actuator capacitance	1550 nF	220 nF
typical step size (min .. max)	0.1 .. 3 µm	10 .. 500 nm
fine positioning range	7.5 µm	1.2 µm

Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 - 10 % depending on load

Position Encoder	
encoder options	0

