

## ANPz30

the smallest stepper positioner for linear, vertical motion

Technology	
travel mechanism	inertial piezo drive

Size and Dimensions	
footprint; height	ø 11; 12 mm
maximum size (outer position)	ø 11; 14.5 mm

Coarse Positioning Mode	
travel (step mode)	2.5 mm
typical minimum step size	25 nm @ 300 K, 5 nm @ 4 K
maximum speed (@ 300 K, no load)	approx. 1 mm/s

Fine Positioning Mode	
scan range	0 .. 5 µm @ 300 K, 0 .. 0.8 µm @ 4 K
scan resolution	sub-nm resolution

Materials (non-magnetic)	
positioner body	Titanium (other materials on request)
actuator	PZT ceramics
connecting wires	insulated twisted pair, Cu
weight	3.8 g

Load	
maximum vertical load	10 g
maximum static forces along the axis	0.3 N
maximum dynamic force along the axis	0.2 N
maximum torque on the axis	1 Ncm

Mounting	
frontside mounting	---
backside mounting	two screws M2 x 1 mm
load mounting	two threads M1.6 x 1 mm

Article Numbers			
/RT Version	1000028	/LT Version	1000006
/HV Version	1000046	/LT/HV Version	1000406
/UHV Version	1000013	/LT/UHV Version	1000019

Compatibility with Electronics	
ANC106 piezo step controller	/RT version only
ANC150 piezo step controller	all versions
ANC200 piezo scan controller	all versions
ANC300 piezo positioning controller	all versions

Working Conditions	
mounting orientation	axis vertical
magnetic field range	0 .. 31 T
temperature range (/RT, /HV, /UHV)	0 .. 100 °C
temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 300 K
max. bake out temperature (/UHV, /LT/UHV)	150 °C
minimum pressure (/RT, /LT)	1E-4 mbar
minimum pressure (/HV, /LT/HV)	1E-8 mbar
minimum pressure (/UHV, /LT/UHV)	5E-11 mbar

Connectors and Feedthroughs	/RT, /LT Versions	all /HV, /UHV Versions
connector type	2-pole pin plug, ø 0.5 mm, d = 2 mm,	two female conn., for pin ø 1 mm,
connector type	30 cm cable with connector	30 cm cable with connector
electrical feedthrough solution	COC230/LT	COC230/HV, COC230/UHV

Temperature Dependent Data	@ 300K	@ 4K (only /LT versions)
input voltage range	0 .. +100 V	0 .. +100 V
typical actuator capacitance	1050 nF	150 nF
typical step size (min .. max)	0.025.. 1 µm	5 .. 250 nm @ 4 K
fine positioning range	5 µm	0.8 µm

Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 - 10 % depending on load

Position Encoder	
encoder options	---

