

ANSxy100

large range xy-scanner

Technology			
travel mechanism	piezo driven lever arm mechanism		
Size and Dimensions			
footprint; height	24 x 24; 10 mm		
Fine Positioning Mode			
scan range	40 x 40 μm^2 @ 300 K, 30 x 30 μm^2 @ 4 K		
scan resolution	sub-nm resolution		
Coarse Positioning Mode			
travel (step mode)	no coarse positioning capability		
Materials (non-magnetic)			
positioner body	Titanium (other materials on request)		
actuator	PZT ceramics		
connecting wires	2 twisted pairs, Cu wires		
weight	18 g		
Load			
maximum vertical load	100 g		
maximum torque on the axis	20 Ncm		
maximum bandwidth	100 Hz		
Mounting			
frontside mounting	two through holes for M2		
backside mounting	two threads M2.5 x 4 mm		
load mounting	six threads M2 x 3 mm		
Article Numbers			
/RT Version	1000557	/LT Version	1000352
/HV Version	1000731	/LT/HV Version	1001092
/UHV Version	1000674	/LT/UHV Version	1000678
Compatibility with Electronics			
ANC300 piezo positioning controller	all versions		
ANC350 piezo controller	all versions		

Working Conditions	
mounting orientation	scanner moving horizontally
magnetic field range	0 .. 31 T
temperature range (/RT, /HV, /UHV)	0 .. 100 °C
temperature range (/LT, /LT/HV, /LT/UHV)	10 mK .. 373 K, Test @ 4.2 K
max. bake out temperature (/UHV, /LT/UHV)	150 °C
minimum pressure (/RT, /LT)	1E-4 mbar
minimum pressure (/HV, /LT/HV)	1E-8 mbar
minimum pressure (/UHV, /LT/UHV)	5E-11 mbar

Connectors and Feedthroughs	/RT, /LT Versions	all /HV, /UHV Versions
connector type	two 2-pole pin plugs, \varnothing 0.5 mm, d = 2 mm,	two 2-pole pin plugs (PEEK), \varnothing 0.5 mm, d = 2 mm,
connector type	30 cm cable with connector	30 cm cable with connector
electrical feedthrough solution	COC230/LT	COC230/HV, COC230/UHV

Temperature Dependent Data	@ 300K	@ 4K (only /LT versions)
input voltage range	0 .. +60 V	0 .. +150 V
typical actuator capacitance	5400, 5400 nF	750, 750 nF
typical step size (min .. max)	---	---
fine positioning range	40 x 40 μm^2	30 x 30 μm^2

Accuracy of Movement	
repeatability	typically 0.1 %
resonance frequency (typically higher than)	---
creep	typically 0.5 - 0.8 % per decade of time
linearity	typically 5 - 10 %

